

SUPERTRACK

Z12NK4 Ku-BAND Maritime VSAT Antenna

The SuperTrack Z-Series is the perfect solution for ships looking for broadband speeds at sea. Stay in touch with your networks via high speed access to the internet, email, multiple VoIP phones and more



MOST SELECTED VSAT MODEL

Most customers in worldwide maritime industry have chosen SUPERTRACK Z-Series as standard VSAT system for their vessels. The Z-Series MK4 will be a optimal satellite communication performance to your vessels.

EASY MAINTENANCE

The Z12MK4 has minimized parts and PCU integrated all electric parts in one module. This feature allows easier maintenance of operators and service providers.

GYRO FREE SUPPORTING

Z12MK4 can support your connection even the vessel does not have gyro(s) or in any case of the gyro failure. Z12MK4 will sustain your network communication with tracking performance without vessel failure status related.

COST AFFORDABLE

With all the latest innovations, SUPERTRACK Z-Series MK4 promise a product line-up which can fulfil all your needs at affordable costs.

RELIABILITY, THE BASIC VIRTUE

In the middle of sea, under various tough sea condition the most important factor or lifeline is high quality communication equipment with reliable connection, stable tracking and fast network performance. Live chatting with friends, video call with family, listening radio over IP, emergency phone calls and all kinds of communication to home-world require network sustainability with reliable equipment.

The SUPERTRACK is your reliable partner all the time.

*Design is subject to change without notice

PRODUCT KEY FEATURES

- In-built DVB-S2X Tuner
 - Carrier SNR direct tracking is available
- Easy Maintenance with simple modular design All electrical control parts are integrated in one single module "PCU" for fast and easy maintenance.
- Web interface & Remote software upgrade Monitoring and Control (M&C) function and firmware upgrade fully supported via web interface.
- Graphic monitoring support

Antenna signal strength or RSSD can be monitored through web GUI via PC and other wireless device such as tablet PC and mobile phone.

• Wi-Fi support

ACU can be operated by Wi-fi interface, a seamless wireless interface between user and ACU

- Proven LEO/MEO satellites tracking algorithm
- Option for single cable solution between ADU and BDU
- SNMP support
- Automatic Satellite Search & Skew Control
- Accurate Signal Acquisition by KNS's Distinctive Algorithm
- Pre-programmed Satellite Database Editable 80 satellite data



Z12NK4 Ku -BAND Maritime VSAT Antenna

SPECIFICATIONS

ABOVE DECK

| Dish Diameter | 120cm (47") |
|---------------------------|--|
| Antenna Dimension | 161cm(D) x 163cm(H) |
| Antenna Weight | 120 Kg |
| Frequency | TX : 13.75 ~ 14.5 GHz |
| | RX : 10.7 ~ 12.75 GHz |
| Antenna Gain | TX : 42.87 dBi @ 14.25 GHz |
| | RX : 40.95 dBi @ 11.75 GHz |
| G/T | 20.79 dB/k(in Radome) |
| | @ 30deg. Elevation angle |
| | and 11.75GHz, Clear Sky |
| Operating Platform | 3 - Axis |
| LNB | Universal LNB (4LO selectable PLL LNB) |
| BUC | 8W |
| OpenAMIP | Support |
| Skew Control | Automatic |
| Elevation Angle | -10° to +110° |
| Azimuth Angle | Unlimited |
| Cross Angle | ± 35° |
| Ship Motion | Roll : ±24° at 8-12 sec periods |
| | Pitch : ±14° at 6-12 sec periods |
| | Yaw : ±8° at 15-20 sec periods |
| Tracking Speed | More than 90°/sec |
| Vibration Damper | Rubber Damper |
| Antenna Input Power | 48V DC, 4.18A |
| Temperature | -20°C to +55°C |
| Humidity | Up to 100% @ 40°C |

PACKING DIMENSION

Size Gross Weight Packed by 174 X 174 X 190 cm 269 kg Wooden Crate

CERTIFICATION/QUALIFICATION

Certification

RoHS

*Specification is subject to change without notice



KNS Headquarters 1476-55, Yuseong-daero, Yuseong-gu, Daejeon South Korea (34055) Tel : +82 42 932 0351 Fax : +82 42 932 0353 E-mail : sales@kns-kr.com

BELOW DECK

KA - 190 Antenna Control unit




| ACU Size | 19" Rack 1U size |
|----------------|--------------------------------------|
| Gyro Interface | NMEA 0183, Synchro, Step by Step |
| Input Power | 100~240V AC, 8A/4A, 50~60 Hz |
| Out put Power | 48VDC, 4.18A |
| External I/O | RS-232C, RS-422, USB, Mini-USB, |
| | Ethernet, Console |
| Monitoring | Web Interface Support (SCS) |
| Wi-fi Dongle | Wi-fi access is available (Optional) |

WARRANTY INFORMATION

3-year parts warranty

RADOME DIMENSION



KNS Malaysia Sales Office

20 Jalan Setia Tropika 9/15, Taman Setia Tropika, Johor, Malaysia Tel : +60 1673 18407 E-mail : james@kns-kr.com

KNS Europe Sales Office

Carl-Zeiss Straße 4, 71093 Weil im Schönbuch, Germany Tel : +49 1727 640 257 E-mail : fpollak@kns-kr.com